



JW LIGHTS M BATHROOM

Blk69 Toa Payoh Lor 4 #01-371 S(310069)

+65 6980 5207 | +65 9878 2388

www.jinwang.com.sg

LED DOWNLIGHTS



www.jinwang.com.sg



266-WH-9W-3000K/4100K/6500K

DIMENSION: $\Phi 120 \times H30 \text{mm}$
CUT HOLE: $\Phi 95 \text{mm}$
LUMINOUS FLUX: 1080 Lm
POWER CONSUMPTION: 9 Watt
COLOR RENDERING: $Ra > 90$
LUMEN PER WATT: 120 Lm/Watt
LED CHIP: Bridgelux
BEAM ANGLE: 120°
COLOR TEM: 3000K/4100K/6500K



266-WH-13W-3000K/4100K/6500K

DIMENSION: $\Phi 145 \times H30 \text{mm}$
CUT HOLE: $\Phi 120 \text{mm}$
LUMINOUS FLUX: 1560 Lm
POWER CONSUMPTION: 13 Watt
COLOR RENDERING: $Ra > 90$
LUMEN PER WATT: 120 Lm/Watt
LED CHIP: Bridgelux
BEAM ANGLE: 120°
COLOR TEM: 3000K/4100K/6500K



366-WH-9W-3000K/4100K/6500K

DIMENSION: $L120 \times W120 \times H30 \text{mm}$
CUT HOLE: $L105 \times H105 \text{mm}$
LUMINOUS FLUX: 1080 Lm
POWER CONSUMPTION: 9 Watt
COLOR RENDERING: $Ra > 90$
LUMEN PER WATT: 120 Lm/Watt
LED CHIP: Bridgelux
BEAM ANGLE: 120°
COLOR TEM: 3000K/4100K/6500K



366-WH-13W-3000K/4100K/6500K

DIMENSION: $L150 \times W150 \times H30 \text{mm}$
CUT HOLE: $L135 \times H135 \text{mm}$
LUMINOUS FLUX: 1560 Lm
POWER CONSUMPTION: 13 Watt
COLOR RENDERING: $Ra > 90$
LUMEN PER WATT: 120 Lm/Watt
LED CHIP: Bridgelux
BEAM ANGLE: 120°
COLOR TEM: 3000K/4100K/6500K





JW LIGHTS M BATHROOM

Blk69 Toa Payoh Lor 4 #01-371 S(310069)

+65 6980 5207 | +65 9878 2388

LED DOWNLIGHTS



761-WH-5W-3000K/4000K
761-BK-5W-3000K/4000K



761-WH-7W-3000K/4000K
761-BK-7W-3000K/4000K



761-WH-10W-MCCT



DIMENSION: $\Phi 50 \times H48 \text{mm}$
CUT HOLE: $\Phi 45 \text{mm}$
LUMINOUS FLUX: 625 Lm
POWER CONSUMPTION: 5 Watt
COLOR RENDERING: $Ra > 97$
LUMEN PER WATT: 125 Lm/Watt
LED CHIP: Bridgelux
BEAM ANGLE: 36°
COLOR TEMPERATURE: 3000K/4000K

DIMENSION: $\Phi 63 \times H62 \text{mm}$
CUT HOLE: $\Phi 55 \text{mm}$
LUMINOUS FLUX: 875 Lm
POWER CONSUMPTION: 7 Watt
COLOR RENDERING: $Ra > 97$
LUMEN PER WATT: 125 Lm/Watt
LED CHIP: Bridgelux
BEAM ANGLE: 36°
COLOR TEMPERATURE: 3000K/4000K

DIMENSION: $\Phi 83 \times H76 \text{mm}$
CUT HOLE: $\Phi 75 \text{mm}$
LUMINOUS FLUX: 1250 Lm
POWER CONSUMPTION: 10 Watt
COLOR RENDERING: $Ra > 97$
LUMEN PER WATT: 125 Lm/Watt
LED CHIP: Bridgelux
BEAM ANGLE: 36°
COLOR TEMPERATURE: CCT



695-WH+WH-3W-3000K/4000K



DIMENSION: $\Phi 40 \times H29 \text{mm}$
CUT HOLE: $\Phi 35 \text{mm}$
LUMINOUS FLUX: 375 Lm
POWER CONSUMPTION: 3 Watt
COLOR RENDERING: $Ra > 97$
LUMEN PER WATT: 125 Lm/Watt
LED CHIP: OSRAM
BEAM ANGLE: 24°
COLOR TEMPERATURE: 3000K/4000K

696-WH-2W-3000K/4000K/6000K
696-BK-2W-3000K/4000K/6000K



DIMENSION: $\Phi 30 \times H50 \text{mm}$
CUT HOLE: $\Phi 25 \text{mm}$
LUMINOUS FLUX: 250 Lm
POWER CONSUMPTION: 2 Watt
COLOR RENDERING: $Ra > 97$
LUMEN PER WATT: 125 Lm/Watt
LED CHIP: OSRAM
BEAM ANGLE: 24°
COLOR TEMPERATURE: 3000K/4000K/6000K