



JW LIGHTS M BATHROOM
Blk69 Toa Payoh Lor 4 #01-371 S(310069)
+65 6980 5207 | +65 9878 2388

www.jinwang.com.sg

www.jinwang.com.sg

ANTI-GLARE SMART DOWNLIGHTS

Smart downlights enhance aesthetics by providing focused illumination that accentuates architectural details and textures. Whether it's for your living room or bedroom, LUMINOUS Downlights deliver high-quality lighting that elevates your space.





JW LIGHTS M BATHROOM
Blk69 Toa Payoh Lor 4 #01-371 S(310069)
+65 6980 5207 | +65 9878 2388

**LED SMART
DOWNLIGHTS**

1 | SMART DOWNLIGHT FITTINGS

Intelligent Power Driver

The following power drivers can be installed according to personal needs or different scenarios.



2.4G-Drive



MCCT-Drive

With Memory Function



Zigbee-Drive



R-Ble&Mesh-Drive

Bluetooth+Tuya



Ble&Mesh-Drive

Bluetooth+Tuya





JW LIGHTS m BATHROOM

Blk69 Toa Payoh Lor 4 #01-371 S(310069)

+65 6980 5207 | +65 9878 2388

www.jinwang.com.sg

LED SMART DOWNLIGHTS



719-WH+BK-10W-CCT/2.4G

DIMENSION:	Φ58xH60mm
CUT HOLE:	Φ50mm
LUMINOUS FLUX:	1250 Lm
POWER CONSUMPTION:	10 Watt
COLOR RENDERING:	Ra>97
LUMEN PER WATT:	125 Lm/Watt
LED CHIP:	Bridgelux
BEAM ANGLE:	36°
COLOR TEMPERATURE:	CCT
SMART MODULE:	2.4G

720-WH+WH-7W-CCT/2.4G

DIMENSION:	Φ94xH68mm
CUT HOLE:	Φ56mm
LUMINOUS FLUX:	875 Lm
POWER CONSUMPTION:	7 Watt
COLOR RENDERING:	Ra>97
LUMEN PER WATT:	125 Lm/Watt
LED CHIP:	Bridgelux
BEAM ANGLE:	36°
COLOR TEMPERATURE:	CCT
SMART MODULE:	2.4G

721-WH+WH-7W-CCT/2.4G

DIMENSION:	Φ85xH55mm
CUT HOLE:	Φ75mm
LUMINOUS FLUX:	840 Lm
POWER CONSUMPTION:	7 Watt
COLOR RENDERING:	Ra>90
LUMEN PER WATT:	120 Lm/Watt
LED CHIP:	Bridgelux
BEAM ANGLE:	36°
COLOR TEMPERATURE:	CCT
SMART MODULE:	2.4G

719-WH+BK-12W-CCT/2.4G

DIMENSION:	Φ70xH65mm
CUT HOLE:	Φ55mm
LUMINOUS FLUX:	1500 Lm
POWER CONSUMPTION:	12 Watt
COLOR RENDERING:	Ra>97
LUMEN PER WATT:	125 Lm/Watt
LED CHIP:	Bridgelux
BEAM ANGLE:	36°
COLOR TEMPERATURE:	CCT
SMART MODULE:	2.4G

720-WH+WH-12W-CCT/2.4G

DIMENSION:	Φ117xH84mm
CUT HOLE:	Φ78mm
LUMINOUS FLUX:	1500 Lm
POWER CONSUMPTION:	12 Watt
COLOR RENDERING:	Ra>97
LUMEN PER WATT:	125 Lm/Watt
LED CHIP:	Bridgelux
BEAM ANGLE:	36°
COLOR TEMPERATURE:	CCT
SMART MODULE:	2.4G

721-WH+WH-12W-CCT/2.4G

DIMENSION:	Φ101xH65mm
CUT HOLE:	Φ90mm
LUMINOUS FLUX:	1500 Lm
POWER CONSUMPTION:	12 Watt
COLOR RENDERING:	Ra>90
LUMEN PER WATT:	120 Lm/Watt
LED CHIP:	Bridgelux
BEAM ANGLE:	36°
COLOR TEMPERATURE:	CCT
SMART MODULE:	2.4G



JW LIGHTS M BATHROOM

Blk69 Toa Payoh Lor 4 #01-371 S(310069)

+65 6980 5207 | +65 9878 2388

www.jinwang.com.sg

LED SMART DOWNLIGHTS



725-WH-10W
3000K/4000K/65000K/CCT/MCCT/2.4G

DIMENSION: $\Phi 105 \times H50 \text{mm}$
CUT HOLE: $\Phi 90 \text{mm}$
LUMINOUS FLUX: 1200 Lm
POWER CONSUMPTION: 10 Watt
COLOR RENDERING: $Ra > 90$
LUMEN PER WATT: 120 Lm/Watt
LED CHIP: Bridgelux
BEAM ANGLE: 36°
COLOR TEM: 3000K/4000K/6500K/CCT
SMART MODULE: 2.4G

723-WH+BK-12W-2.5"-CCT/MCCT/2.4G
723-WH+WH-12W-2.5"-CCT/MCCT/2.4G

DIMENSION: $\Phi 85 \times H64 \text{mm}$
CUT HOLE: $\Phi 75 \text{mm}$
LUMINOUS FLUX: 1500 Lm
POWER CONSUMPTION: 12 Watt
COLOR RENDERING: $Ra > 97$
LUMEN PER WATT: 125 Lm/Watt
LED CHIP: Bridgelux
BEAM ANGLE: 36°
COLOR TEMPERATURE: CCT
SMART MODULE: 2.4G

725-WH-15W-CCT/MCCT/2.4G

DIMENSION: $\Phi 130 \times H58 \text{mm}$
CUT HOLE: $\Phi 120 \text{mm}$
LUMINOUS FLUX: 1800 Lm
POWER CONSUMPTION: 15 Watt
COLOR RENDERING: $Ra > 90$
LUMEN PER WATT: 120 Lm/Watt
LED CHIP: Bridgelux
BEAM ANGLE: 36°
COLOR TEMPERATURE: CCT
SMART MODULE: 2.4G

727-WH+SR-12W-CCT/MCCT/2.4G
727-WH+BK-12W-CCT/MCCT/2.4G

DIMENSION: $\Phi 85 \times H85 \text{mm}$
CUT HOLE: $\Phi 75 \text{mm}$
LUMINOUS FLUX: 1500 Lm
POWER CONSUMPTION: 12 Watt
COLOR RENDERING: $Ra > 97$
LUMEN PER WATT: 125 Lm/Watt
LED CHIP: Bridgelux
BEAM ANGLE: 36°
COLOR TEMPERATURE: CCT
SMART MODULE: 2.4G



JW LIGHTS M BATHROOM

Blk69 Toa Payoh Lor 4 #01-371 S(310069)

+65 6980 5207 | +65 9878 2388

www.jinwang.com.sg

LED SMART DOWNLIGHTS



693-1L-WH-10W-CCT/MCCT/2.4G
693-1L-BK-10W-CCT/MCCT/2.4G



DIMENSION:	Φ88xH33mm
CUT HOLE:	Φ75mm
LUMINOUS FLUX:	1250 Lm
POWER CONSUMPTION:	10 Watt
COLOR RENDERING:	Ra>97
LUMEN PER WATT:	125 Lm/Watt
LED CHIP:	Bridgelux
BEAM ANGLE:	36°
COLOR TEMPERATURE:	CCT
SMART MODULE:	2.4G

693-2L-WH-15W-CCT/MCCT/2.4G
693-2L-BK-15W-CCT/MCCT/2.4G



DIMENSION:	L177xW88xH33mm
CUT HOLE:	L160xH75mm
LUMINOUS FLUX:	1875 Lm
POWER CONSUMPTION:	15 Watt
COLOR RENDERING:	Ra>97
LUMEN PER WATT:	125 Lm/Watt
LED CHIP:	Bridgelux
BEAM ANGLE:	36°
COLOR TEMPERATURE:	CCT
SMART MODULE:	2.4G



JW LIGHTS m BATHROOM

Blk69 Toa Payoh Lor 4 #01-371 S(310069)

+65 6980 5207 | +65 9878 2388

LED SMART DOWNLIGHTS



772-WH-12W-CCT/MCCT/2.4G
772-BK-12W-CCT/MCCT/2.4G



778-WH-12W-CCT/MCCT/2.4G



779-WH-12W-CCT/MCCT/2.4G
779-BK-12W-CCT/MCCT/2.4G



DIMENSION: $\Phi 85 \times H 77 \text{mm}$
CUT HOLE: $\Phi 75 \text{mm}$
LUMINOUS FLUX: 1500 Lm
POWER CONSUMPTION: 12 Watt
COLOR RENDERING: $Ra > 97$
LUMEN PER WATT: 125 Lm/Watt
LED CHIP: Bridgelux
BEAM ANGLE: 36°
COLOR TEMPERATURE: CCT
SMART MODULE: 2.4G

DIMENSION: $\Phi 82 \times H 51 \text{mm}$
CUT HOLE: $\Phi 75 \text{mm}$
LUMINOUS FLUX: 1500 Lm
POWER CONSUMPTION: 12 Watt
COLOR RENDERING: $Ra > 97$
LUMEN PER WATT: 125 Lm/Watt
LED CHIP: Bridgelux
BEAM ANGLE: 36°
COLOR TEMPERATURE: CCT
SMART MODULE: 2.4G

DIMENSION: $\Phi 100 \times H 65 \text{mm}$
CUT HOLE: $\Phi 90 \text{mm}$
LUMINOUS FLUX: 1500 Lm
POWER CONSUMPTION: 12 Watt
COLOR RENDERING: $Ra > 97$
LUMEN PER WATT: 125 Lm/Watt
LED CHIP: Bridgelux
BEAM ANGLE: 36°
COLOR TEMPERATURE: CCT
SMART MODULE: 2.4G



786-WH-12W-CCT/MCCT/2.4G



790-WH-10W-CCT/MCCT/2.4G



791-WH-12W-CCT/MCCT/2.4G



DIMENSION: $\Phi 82 \times H 60 \text{mm}$
CUT HOLE: $\Phi 75 \text{mm}$
LUMINOUS FLUX: 1500 Lm
POWER CONSUMPTION: 12 Watt
COLOR RENDERING: $Ra > 97$
LUMEN PER WATT: 125 Lm/Watt
LED CHIP: Bridgelux
BEAM ANGLE: 36°
COLOR TEMPERATURE: CCT
SMART MODULE: 2.4G

DIMENSION: $\Phi 85 \times H 58 \text{mm}$
CUT HOLE: $\Phi 75 \text{mm}$
LUMINOUS FLUX: 1250 Lm
POWER CONSUMPTION: 10 Watt
COLOR RENDERING: $Ra > 97$
LUMEN PER WATT: 125 Lm/Watt
LED CHIP: Bridgelux
BEAM ANGLE: 36°
COLOR TEMPERATURE: CCT
SMART MODULE: 2.4G

DIMENSION: $\Phi 85 \times H 78 \text{mm}$
CUT HOLE: $\Phi 75 \text{mm}$
LUMINOUS FLUX: 1500 Lm
POWER CONSUMPTION: 12 Watt
COLOR RENDERING: $Ra > 97$
LUMEN PER WATT: 125 Lm/Watt
LED CHIP: Bridgelux
BEAM ANGLE: 36°
COLOR TEMPERATURE: CCT
SMART MODULE: 2.4G



JW LIGHTS m BATHROOM

Blk69 Toa Payoh Lor 4 #01-371 S(310069)

+65 6980 5207 | +65 9878 2388

www.jinwang.com.sg

LED SMART DOWNLIGHTS



780-1G-WH-12W-CCT/2.4G
780-1G-BK-12W-CCT/2.4G



DIMENSION: $\Phi 85 \times H 85 \text{ mm}$
LUMINOUS FLUX: 1500 Lm
POWER CONSUMPTION: 12 Watt
COLOR RENDERING: $R_a > 97$
LUMEN PER WATT: 125 Lm/Watt
LED CHIP: Bridgelux
BEAM ANGLE: 60°
COLOR TEMPERATURE: CCT
SMART MODULE: 2.4G

780-2G-WH-24W-CCT/2.4G
780-2G-BK-24W-CCT/2.4G



DIMENSION: $L 220 \times \Phi 85 \times H 88 \text{ mm}$
LUMINOUS FLUX: 3000 Lm
POWER CONSUMPTION: 24 Watt
COLOR RENDERING: $R_a > 97$
LUMEN PER WATT: 125 Lm/Watt
LED CHIP: Bridgelux
BEAM ANGLE: 60°
COLOR TEMPERATURE: CCT
SMART MODULE: 2.4G



JW LIGHTS m BATHROOM

Blk69 Toa Payoh Lor 4 #01-371 S(310069)

+65 6980 5207 | +65 9878 2388

www.jinwang.com.sg

LED SMART DOWNLIGHTS

www.jinwang.com.sg



763-WH-10W-CCT/2.4G
763-BK-10W-CCT/2.4G



765-WH-10W-CCT/2.4G
765-BK-10W-CCT/2.4G



793-WH-10W-CCT/2.4G
793-BK-10W-CCT/2.4G



DIMENSION: $\Phi 85 \times H 88 \text{mm}$
LUMINOUS FLUX: 1200 Lm
POWER CONSUMPTION: 10 Watt
COLOR RENDERING: $Ra > 90$
LUMEN PER WATT: 120 Lm/Watt
LED CHIP: Bridgelux
BEAM ANGLE: 100°
COLOR TEMPERATURE: CCT
SMART MODULE: 2.4G

DIMENSION: $\Phi 83 \times H 85 \text{mm}$
LUMINOUS FLUX: 1200 Lm
POWER CONSUMPTION: 10 Watt
COLOR RENDERING: $Ra > 90$
LUMEN PER WATT: 120 Lm/Watt
LED CHIP: Bridgelux
BEAM ANGLE: 100°
COLOR TEMPERATURE: CCT
SMART MODULE: 2.4G

DIMENSION: $\Phi 90 \times H 70 \text{mm}$
LUMINOUS FLUX: 1250 Lm
POWER CONSUMPTION: 10 Watt
COLOR RENDERING: $Ra > 97$
LUMEN PER WATT: 125 Lm/Watt
LED CHIP: Bridgelux
BEAM ANGLE: 120°
COLOR TEMPERATURE: CCT
SMART MODULE: 2.4G



781-WH-12W-CCT/2.4G
781-BK-12W-CCT/2.4G



782-WH-12W-CCT/2.4G
782-BK-12W-CCT/2.4G



783-WH-12W-CCT/2.4G
783-BK-12W-CCT/2.4G



DIMENSION: $\Phi 85 \times H 100 \text{mm}$
LUMINOUS FLUX: 1440 Lm
POWER CONSUMPTION: 12 Watt
COLOR RENDERING: $Ra > 90$
LUMEN PER WATT: 120 Lm/Watt
LED CHIP: Bridgelux
BEAM ANGLE: 36°
COLOR TEMPERATURE: CCT
SMART MODULE: 2.4G

DIMENSION: $\Phi 87 \times H 110 \text{mm}$
LUMINOUS FLUX: 1500 Lm
POWER CONSUMPTION: 12 Watt
COLOR RENDERING: $Ra > 97$
LUMEN PER WATT: 125 Lm/Watt
LED CHIP: Bridgelux
BEAM ANGLE: 36°
COLOR TEMPERATURE: CCT
SMART MODULE: 2.4G

DIMENSION: $\Phi 87 \times H 110 \text{mm}$
LUMINOUS FLUX: 1440 Lm
POWER CONSUMPTION: 12 Watt
COLOR RENDERING: $Ra > 90$
LUMEN PER WATT: 120 Lm/Watt
LED CHIP: Bridgelux
BEAM ANGLE: 36°
COLOR TEMPERATURE: CCT
SMART MODULE: 2.4G



JW LIGHTS m BATHROOM

Blk69 Toa Payoh Lor 4 #01-371 S(310069)

+65 6980 5207 | +65 9878 2388

www.jinwang.com.sg

LED DOWNLIGHTS



711-WH-12W-CCT/MCCT/2.4G
711-BK-12W-CCT/MCCT/2.4G



DIMENSION: $\Phi 120 \times H 70 \text{ mm}$
LUMINOUS FLUX: 1440 Lm
POWER CONSUMPTION: 12 Watt
COLOR RENDERING: $R_a > 90$
LUMEN PER WATT: 120 Lm/Watt
LED CHIP: Bridgelux
BEAM ANGLE: 120°
COLOR TEMPERATURE: CCT
SMART MODULE: 2.4G

713-WH-12W-CCT/MCCT/2.4G
713-BK-12W-CCT/MCCT/2.4G



DIMENSION: $\Phi 120 \times H 75 \text{ mm}$
LUMINOUS FLUX: 1440 Lm
POWER CONSUMPTION: 12 Watt
COLOR RENDERING: $R_a > 90$
LUMEN PER WATT: 120 Lm/Watt
LED CHIP: Bridgelux
BEAM ANGLE: 120°
COLOR TEMPERATURE: CCT
SMART MODULE: 2.4G

715-WH-12W-CCT/MCCT/2.4G
715-BK-12W-CCT/MCCT/2.4G



DIMENSION: $\Phi 120 \times H 65 \text{ mm}$
LUMINOUS FLUX: 1440 Lm
POWER CONSUMPTION: 12 Watt
COLOR RENDERING: $R_a > 90$
LUMEN PER WATT: 120 Lm/Watt
LED CHIP: Bridgelux
BEAM ANGLE: 120°
COLOR TEMPERATURE: CCT
SMART MODULE: 2.4G



JW LIGHTS m BATHROOM

Blk69 Toa Payoh Lor 4 #01-371 S(310069)

+65 6980 5207 | +65 9878 2388

LED DOWNLIGHTS



350°Rotation

60°Selective Folding



360°Rotation

90°Vertical adjustment

716-WH-8W-RGB
716-BK-8W-RGB



DIMENSION: L150xW150xH30mm
LUMINOUS FLUX: 1000 Lm
POWER CONSUMPTION: 8 Watt
COLOR RENDERING: Ra>97
LUMEN PER WATT: 125 Lm/Watt
LED CHIP: COB
BEAM ANGLE: 36°
COLOR TEMPERATURE: RGB

771-WH-8W-CCT/MCCT/2.4G
771-BK-8W-CCT/MCCT/2.4G



DIMENSION: Φ85xH67.5mm
CUT HOLE: Φ75mm
LUMINOUS FLUX: 1000 Lm
POWER CONSUMPTION: 8 Watt
COLOR RENDERING: Ra>97
LUMEN PER WATT: 125 Lm/Watt
LED CHIP: COB
BEAM ANGLE: 36°
COLOR TEMPERATURE: CCT
SMART MODULE: 2.4G



JW LIGHTS m BATHROOM

Blk69 Toa Payoh Lor 4 #01-371 S(310069)

+65 6980 5207 | +65 9878 2388

www.jinwang.com.sg

LED DOWNLIGHTS

www.jinwang.com.sg



750-5L-WH-10W-3000K/4000K
750-5L-BK-10W-3000K/4000K

750-10L-WH-20W-3000K/4000K
750-10L-BK-20W-3000K/4000K

DIMENSION: L165xW62xH50mm
CUT HOLE: L155xW55mm
LUMINOUS FLUX: 1250 Lm
POWER CONSUMPTION: 10 Watt
COLOR RENDERING: Ra>97
LUMEN PER WATT: 125 Lm/Watt
LED CHIP: Bridgelux
BEAM ANGLE: 75°
COLOR TEMPERATURE: 3000K/4000K

DIMENSION: L298xW65xH50mm
CUT HOLE: L290xW55mm
LUMINOUS FLUX: 2500 Lm
POWER CONSUMPTION: 20 Watt
COLOR RENDERING: Ra>97
LUMEN PER WATT: 125 Lm/Watt
LED CHIP: Bridgelux
BEAM ANGLE: 75°
COLOR TEMPERATURE: 3000K/4000K



751-5L-WH-10W-3000K/4000K
751-5L-BK-10W-3000K/4000K

751-10L-WH-20W-3000K/4000K
751-10L-BK-20W-3000K/4000K

DIMENSION: L136xW35xH65mm
LUMINOUS FLUX: 1250 Lm
POWER CONSUMPTION: 10 Watt
COLOR RENDERING: Ra>97
LUMEN PER WATT: 125 Lm/Watt
LED CHIP: Bridgelux
BEAM ANGLE: 75°
COLOR TEMPERATURE: 3000K/4000K

DIMENSION: L270xW35xH65mm
LUMINOUS FLUX: 2500 Lm
POWER CONSUMPTION: 20 Watt
COLOR RENDERING: Ra>97
LUMEN PER WATT: 125 Lm/Watt
LED CHIP: Bridgelux
BEAM ANGLE: 75°
COLOR TEMPERATURE: 3000K/4000K

