



JW LIGHTS m BATHROOM
Blk69 Toa Payoh Lor 4 #01-371 S(310069)
+65 6980 5207 | +65 9878 2388

ULTRA-NARROW MAGNETIC TRACK SYSTEM

2 | ULTRA-NARROW MAGNETIC TRACK SYSTEM

The lamp has a safety buckle design with a 10mm ultra-narrow track.
The light positions can be adjusted freely without ceiling reconstruction.

The track can be installed at any desired length,
and splicing allows extension and rotation up to 30 meters.

Intelligent Radio Frequency Remote Control

- Group Control (supports programming for 4 light groups)
- One-click Switch between Warm Light / Daylight / Cool White Light
- Brightness Adjustment (1-100% stepless dimming for brightness)
- Color Temperature Adjustment 3000-6000K stepless tuning
- Quick Code Pairing/Code Clearing

2.4G Remote Control





JW LIGHTS M BATHROOM
Blk69 Toa Payoh Lor 4 #01-371 S(310069)
+65 6980 5207 | +65 9878 2388

ULTRA-NARROW MAGNETIC TRACK SYSTEM



Grille Light

HS10-12T-BK-2.4G

DIMENSION:	L200xW10xH37mm
MATERIAL:	Aluminum Product
LUMINOUS FLUX:	667.53 Lm
POWER CONSUMPTION:	10 Watt
COLOR RENDERING:	Ra>90
LUMEN PER WATT:	63 Lm/Watt
LED CHIP:	Bridgelux
BEAM ANGLE:	38°
INPUT:	DC 48V
COLOR TEMPERATURE:	CCT
SMART MODULE:	2.4G



HS10-12T-BK-2.4G



HS10-24T-BK-2.4G

HS10-24T-BK-2.4G

DIMENSION:	L400xW10xH37mm
MATERIAL:	Aluminum Product
LUMINOUS FLUX:	1287.9 Lm
POWER CONSUMPTION:	20 Watt
COLOR RENDERING:	Ra>90
LUMEN PER WATT:	65.45 Lm/Watt
LED CHIP:	Bridgelux
BEAM ANGLE:	38°
INPUT:	DC 48V
COLOR TEMPERATURE:	CCT
SMART MODULE:	2.4G





JW LIGHTS m BATHROOM
Blk69 Toa Payoh Lor 4 #01-371 S(310069)
+65 6980 5207 | +65 9878 2388

ULTRA-NARROW MAGNETIC TRACK SYSTEM



Floodlight Light

HS10-10F-BK-2.4G

DIMENSION:	L200xW10xH37mm
MATERIAL:	Aluminum Product
LUMINOUS FLUX:	420.75 Lm
POWER CONSUMPTION:	10 Watt
COLOR RENDERING:	Ra>90
LUMEN PER WATT:	40.17 Lm/Watt
LED CHIP:	Bridgelux
BEAM ANGLE:	120°
INPUT:	DC 48V
COLOR TEMPERATURE:	CCT
SMART MODULE:	2.4G

HS10-20F-BK-2.4G

DIMENSION:	L400xW10xH37mm
MATERIAL:	Aluminum Product
LUMINOUS FLUX:	840.77 Lm
POWER CONSUMPTION:	20 Watt
COLOR RENDERING:	Ra>90
LUMEN PER WATT:	40.88 Lm/Watt
LED CHIP:	Bridgelux
BEAM ANGLE:	120°
INPUT:	DC 48V
COLOR TEMPERATURE:	CCT
SMART MODULE:	2.4G

HS10-30F-BK-2.4G

DIMENSION:	L600xW10xH37mm
MATERIAL:	Aluminum Product
LUMINOUS FLUX:	1150 Lm
POWER CONSUMPTION:	30 Watt
COLOR RENDERING:	Ra>90
LUMEN PER WATT:	41.32 Lm/Watt
LED CHIP:	Bridgelux
BEAM ANGLE:	120°
INPUT:	DC 48V
COLOR TEMPERATURE:	CCT
SMART MODULE:	2.4G





JW LIGHTS M BATHROOM
Blk69 Toa Payoh Lor 4 #01-371 S(310069)
+65 6980 5207 | +65 9878 2388

ULTRA-NARROW MAGNETIC TRACK SYSTEM

Folding Grille Light



HS10-ZD-12T-BK-2.4G

DIMENSION:	L200xW10xH73mm
MATERIAL:	Aluminum Product
LUMINOUS FLUX:	667.53 Lm
POWER CONSUMPTION:	10 Watt
COLOR RENDERING:	Ra>90
LUMEN PER WATT:	63 Lm/Watt
LED CHIP:	Bridgelux
BEAM ANGLE:	38°
INPUT:	DC 48V
COLOR TEMPERATURE:	CCT
SMART MODULE:	2.4G





JW LIGHTS m BATHROOM

Blk69 Toa Payoh Lor 4 #01-371 S(310069)

+65 6980 5207 | +65 9878 2388

ULTRA-NARROW MAGNETIC TRACK SYSTEM

Folding Floodlight Light



HS10-ZD-10F-BK-2.4G

DIMENSION:	L200xW10xH73mm
MATERIAL:	Aluminum Product
LUMINOUS FLUX:	420.75 Lm
POWER CONSUMPTION:	10 Watt
COLOR RENDERING:	Ra>90
LUMEN PER WATT:	40.17 Lm/Watt
LED CHIP:	Bridgelux
BEAM ANGLE:	120°
INPUT:	DC 48V
COLOR TEMPERATURE:	CCT
SMART MODULE:	2.4G





JW LIGHTS m BATHROOM
Blk69 Toa Payoh Lor 4 #01-371 S(310069)
+65 6980 5207 | +65 9878 2388

ULTRA-NARROW MAGNETIC TRACK SYSTEM

Convex spotlight



HS10-1TM-BK-2.4G

DIMENSION:	Φ25xH65mm
MATERIAL:	Aluminum Product
LUMINOUS FLUX:	105.09 Lm
POWER CONSUMPTION:	2 Watt
COLOR RENDERING:	Ra>90
LUMEN PER WATT:	39.82 Lm/Watt
LED CHIP:	Bridgelux
BEAM ANGLE:	24°
INPUT:	DC 48V
COLOR TEMPERATURE:	CCT
SMART MODULE:	2.4G

HS10-3TM-BK-2.4G

DIMENSION:	Φ25xL130xH65mm
MATERIAL:	Aluminum Product
LUMINOUS FLUX:	334.73 Lm
POWER CONSUMPTION:	6 Watt
COLOR RENDERING:	Ra>90
LUMEN PER WATT:	52.35 Lm/Watt
LED CHIP:	Bridgelux
BEAM ANGLE:	24°
INPUT:	DC 48V
COLOR TEMPERATURE:	CCT
SMART MODULE:	2.4G





JW LIGHTS m BATHROOM

Blk69 Toa Payoh Lor 4 #01-371 S(310069)

+65 6980 5207 | +65 9878 2388

ULTRA-NARROW MAGNETIC TRACK SYSTEM



HS10-L20-BK-2.4G



HS10-L33-BK-2.4G



HS10-L43-BK-2.4G

Track Light

HS10-L20-BK-2.4G

DIMENSION:	Φ20xL60mm
MATERIAL:	Aluminum Product
LUMINOUS FLUX:	103.4 Lm
POWER CONSUMPTION:	2 Watt
COLOR RENDERING:	Ra>90
LUMEN PER WATT:	33.95 Lm/Watt
LED CHIP:	Bridgelux
BEAM ANGLE:	24°
INPUT:	DC 48V
COLOR TEMPERATURE:	CCT
SMART MODULE:	2.4G

HS10-L33-BK-2.4G

DIMENSION:	Φ33xL85mm
MATERIAL:	Aluminum Product
LUMINOUS FLUX:	374.42 Lm
POWER CONSUMPTION:	6 Watt
COLOR RENDERING:	Ra>90
LUMEN PER WATT:	61.34 Lm/Watt
LED CHIP:	Bridgelux
BEAM ANGLE:	24°
INPUT:	DC 48V
COLOR TEMPERATURE:	CCT
SMART MODULE:	2.4G

HS10-L43-BK-2.4G

DIMENSION:	Φ43xL110mm
MATERIAL:	Aluminum Product
LUMINOUS FLUX:	674.29 Lm
POWER CONSUMPTION:	12 Watt
COLOR RENDERING:	Ra>90
LUMEN PER WATT:	60.26 Lm/Watt
LED CHIP:	Bridgelux
BEAM ANGLE:	24°
INPUT:	DC 48V
COLOR TEMPERATURE:	CCT
SMART MODULE:	2.4G





JW LIGHTS m BATHROOM
Blk69 Toa Payoh Lor 4 #01-371 S(310069)
+65 6980 5207 | +65 9878 2388

ULTRA-NARROW MAGNETIC TRACK SYSTEM

Solar Eclipse Wall Lamp



Solar Eclipse Wall Lamp



HS10-T33-2-BK-2.4G

DIMENSION:	Φ33xL85mm
MATERIAL:	Aluminum Product
LUMINOUS FLUX:	684.1 Lm
POWER CONSUMPTION:	6 Watt*2
COLOR RENDERING:	Ra>90
LUMEN PER WATT:	58.05 Lm/Watt
LED CHIP:	Bridgelux
BEAM ANGLE:	24°
INPUT:	DC 48V
COLOR TEMPERATURE:	CCT
SMART MODULE:	2.4G

HS10-YSBD-BK-2.4G

DIMENSION:	Φ168xH20mm
MATERIAL:	Aluminum Product
LUMINOUS FLUX:	488.45 Lm
POWER CONSUMPTION:	9 Watt
COLOR RENDERING:	Ra>90
LUMEN PER WATT:	46.05 Lm/Watt
LED CHIP:	Bridgelux
BEAM ANGLE:	24°
INPUT:	DC 48V
COLOR TEMPERATURE:	CCT
SMART MODULE:	2.4G





JW LIGHTS M BATHROOM

Blk69 Toa Payoh Lor 4 #01-371 S(310069)

+65 6980 5207 | +65 9878 2388

**ULTRA-NARROW
MAGNETIC TRACK SYSTEM**

Spherical Decorative Lamp - Earth



Spherical Pendant light - Earth



HS10-GDD150-BK-2.4G

DIMENSION:	Φ150xH150mm
MATERIAL:	Aluminum Product
LUMINOUS FLUX:	323.8 Lm
POWER CONSUMPTION:	6 Watt
COLOR RENDERING:	Ra>90
LUMEN PER WATT:	52.38 Lm/Watt
LED CHIP:	Bridgelux
BEAM ANGLE:	360°
INPUT:	DC 48V
COLOR TEMPERATURE:	CCT
SMART MODULE:	2.4G



HS10-D150-BK-2.4G

DIMENSION:	Φ150xH150mm
MATERIAL:	Aluminum Product
LUMINOUS FLUX:	323.8 Lm
POWER CONSUMPTION:	6 Watt
COLOR RENDERING:	Ra>90
LUMEN PER WATT:	52.38 Lm/Watt
LED CHIP:	Bridgelux
BEAM ANGLE:	360°
INPUT:	DC 48V
COLOR TEMPERATURE:	CCT
SMART MODULE:	2.4G





JW LIGHTS M BATHROOM

Blk69 Toa Payoh Lor 4 #01-371 S(310069)

+65 6980 5207 | +65 9878 2388

ULTRA-NARROW MAGNETIC TRACK SYSTEM

Surface/Hanging-Track

HS10-C 1M/2M/3M



HS10-C-L-BK
Horizontal Angle



HS10-DX9
Hanging wire package

Batch Ash Track

HS10-E 1M/2M/3M



HS10-E-L-BK
Horizontal Angle

220V to 48V Power Supply
HS10-100W-BK/HS10-200W-BK

POWER: 100W / 200W
SIZE: L200xW10xH37mm / L250xW10xH37mm

Input Module
HS10-SRMK-BK

SIZE: L50xW10xH37mm
USE: The end of the line is connected to the external transformer
Module connected to rail strip.

Direct Power Module
HS10-ZJ-BK

SIZE: L120xW10xH37mm
USE: Type I bidirectional conductive module, two straight track
splicing power.

Angle Power Module
HS10-RJ-BK

SIZE: L250xW10xH37mm
USE: L-type Angle conduction module, two tracks splicing power.